

FEATURES AND BENEFITS

A safe environmentally friendly alternative to glass media. Our range of thermally bonded non-shedding synthetic medias are fully tested to ISO16890 and are perfect for all kinds of applications including prefilters in air conditioning systems through to specialist paint spraying applications.

Suitable for humidity up to 100%.

Oeko-Tex 100 approved media which means it is free from harmful substances and skin irritants.

Fully incinerable saving on landfill.



APPLICATIONS

Suitable for use on all kinds of air conditioning systems

- Paint shop booth air intakes
- Intakes for heating & ventilation units
- Ceiling fan coil units
- Temporary filtration protection during duct cleaning

PRODUCT OPTIONS AVAILABLE

- Range of filter grades
- Alternative thicknesses
- Various roll sizes available
- Custom made roll and pads pre cut to size

Filterite Ltd

Harolds Court, Saxon Business Park, Bromsgrove, B60 4FL

Tel: 01527 836201 Email: sales@filterite.co.uk

www.filterite.co.uk



Performance Details

Product	ISO 16890 Rating	EN779:2012 Rating	Thickness MM	Standard Stock Roll Size	Surface Weight g/m2	Pressure Loss		Maximum Air Velocity m/s
						Initial (Pa)	Final (Pa)	
FL100	Course 40%	G2	10	1m x 40m	100	25	175	1.5
FL150	Course 50%	G3	15	1m x 20m	150	25	175	1.25
FL220	Course 60%	G4	20	1m x 20m	220	35	175	1.25
FL220	Course 60%	G4	20	2m x 20m	220	35	175	1.25
EA40	Course 60%	G4	45	1m x 10m	400	60	175	1
V500G	Course 85%	M5	25	1m x 10m	550	25	450	0.25
V600G	Course 85%	M5	25	1m x 10m	650	30	450	0.25

Filterite Ltd

Harolds Court, Saxon Business Park, Bromsgrove, B60 4FL

Tel: 01527 836201 **Email:** sales@filterite.co.uk

www.filterite.co.uk

